



MOVILAT 7

ACRYLIC WATER-BASED WALL PAINT

Matt paint for walls and ceilings with slight silky (eggshell) gloss



- Matt paint with slight silky(eggshell) gloss
- Suitable for wet rooms
- Easy-to-wash
- Great spreading capacity
- Fast drying
- Non-dripping, easy-to-apply

DESCRIPTION:

Fast-drying easy-to-apply water-based paint with great adhesion to new and previously painted plaster, concrete, brick, gypsum board and different types of wallpaper surfaces. The paint is characterised by good spreading capacity and resistance to cleaning solutions, significant vapour permeability. Non-dripping during the application. It may be tinted to many shades.

FIELD OF APPLICATION:

Paint is intended for painting of walls and ceilings in dry residential, office, public, etc. areas, as well as in rooms with increased humidity such as bathrooms, toilets, etc. May be used for painting of plaster, concrete, brick and gypsum board and embossed acrylic, vinyl and fiber glass wallpapers, as well as wood-fibre and wood particleboards. This paint may be also applied on primed metal and other surfaces previously painted with water-based paints.

<u>TECHNICAL PARAMETERS:</u>	
<u>Colour:</u>	White (A base) which may be tinted in to light shades. C base may be tinted to dark shades using RILAKOLOR tinting system. Total number of shades - more than 16,000.
<u>Gloss:</u>	Matt with slight silk gloss. Degree of gloss – 7
<u>Drying time at 20°C temperature:</u>	1 hour
<u>Resistance to wet friction:</u>	Not less than 2000 cycles (DIN 53778); Class 1 (ISO 11998)
<u>Consumption:</u>	8÷12 m ² /l
<u>Solvent:</u>	Water
<u>Tools used for application:</u>	Brush, roller, paint sprayer.
<u>Storage period:</u>	36 months in tightly closed manufacturer's container at the temperature exceeding +5 ⁰ C.
<u>Packaging:</u>	0.9 l; 3.6 l; 9 l.



APPLICATION:

PREPARATION OF PAINT FOR USE:

Mix paint well before application. Dilute with water till required viscosity, if necessary.

PREPARATION OF SURFACE:

Clean off any dust, dirt, chalk, previously painted coat of glue paint or other type of old flaked paint. Treat the oil- or alkyd-painted surfaces with sandpaper until light-matte appearance is reached.

PRIMING OF SURFACE:

Porous plaster and concrete surfaces should be primed using MOVILAT BASE, FORAKRIL BASE, AKROPRIM. MOVILAT 7 itself can also be used as a primer diluted by water up to 15% of the paint volume.

APPLICATION:

Apply 2 layers to surfaces to be painted. For the application of the first layer, we recommend to dilute the paint with water up to 10%. Application of 1 - 2 layers is recommended in case of repainting of the previously painted surfaces. Air and painted surface temperature may not be lower than + 5°C and higher than + 30°C.

SURFACE TREATMENT:

Cleaning of fresh painted surface is allowed not earlier than one week after painting. A cloth soft or sponge dampened with clean water or weak alkaline cleaning solution may be used for cleaning of the surface. Cleaning should be completed with soft cloth or a sponge dampened with clean water.

TOOL CLEANING:

Use water for cleaning of tools.

ENVIRONMENT AND OCCUPATIONAL SAFETY AND HEALTH PROTECTION:

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



0.9l, 3.6l, 9l



8÷12 m²/l



1 h



RILAKOLOR
(A, C BASE)

