



INTERIOR PROFESSIONAL 7

MATT ACRYLIC PAINT FOR WALLS AND CEILINGS WITH SLIGHT SILKY GLOSS



- Designed for finishing walls and ceilings
- Easy to apply and quick drying
- Excellent resistance to moisture and washing
- Ideal for bathrooms, kitchens, and other humid areas

DESCRIPTION:

Fast-drying, easy-to-apply waterborne paint based on acrylic dispersion. Forms a matt finish with a soft silky sheen. It helps give walls a livelier and "richer" appearance than a completely matte finish and makes maintenance easier (it's easier to wash and it better masks stains). Offers enhanced wash resistance and maintains appearance even after repeated cleaning. Features soft thixotropy, which improves application and workability over large surfaces.

FIELD OF APPLICATION:

Suitable for plastered, concrete, wooden, brick, and gypsum board surfaces in residential, office, and public spaces with medium to high traffic. Also recommended for textured acrylic and fiberglass wallpaper, as well as for high-humidity areas such as bathrooms and restrooms.

<u>TECHNICAL PARAMETERS:</u>	
<u>Colour:</u>	White (A base) which may be tinted in to light shades. C base may be tinted to dark shades using RILAKOLOR tinting system.
<u>Gloss:</u>	matt with a soft silky (satin) sheen
<u>Drying time at 20°C temperature and the relative air humidity 50 %:</u>	1 hour
<u>Solids contents, %</u>	Base A: 50 ± 3; base C: 61 ± 3.
<u>Density, gr/L</u>	Base A: 1,30 ± 0,05; base C: 1,34 ± 0,05
<u>Resistance to wet friction:</u>	Class 1 (ISO 11998)
<u>Consumption:</u>	8÷12 m ² /l
<u>Solvent:</u>	Water
<u>Tools used for application:</u>	Brush, roller, paint sprayer.
<u>Storage period:</u>	36 months in tightly closed manufacturer's container at the temperature exceeding +5°C.
<u>Packaging:</u>	0.9 l; 3.6 l; 9 l.



APPLICATION:

PREPARATION OF PAINT FOR USE:

Mix paint well before application. Dilute with water till required viscosity, if necessary.

PREPARATION OF SURFACE:

Clean off any dust, dirt, chalk, previously painted coat of glue paint or other type of old flaked paint. Treat the oil- or alkyd-painted surfaces with sandpaper until light-matte appearance is reached. If there is mold or another fungal infection, treat it with AKVASEPT solution.

PRIMING OF SURFACE:

Porous plaster and concrete surfaces should be primed using MOVILAT PRIMER, FORAKRIL BASE, AKROPRIM. Interior Professional 7 itself can also be used as a primer diluted by water up to 15% of the paint volume.

Glossy mineral surfaces, such as ceramic tiles or clinker bricks, must first be primed with FORAKRIL BASE penetrating primer before coating.

APPLICATION:

Apply 1-2 layers to surfaces to be painted at an air and surface temperature of at least +5°C and a relative humidity of no more than 85%.

TOOL CLEANING:

Use water for cleaning of tools.

ENVIRONMENT AND OCCUPATIONAL SAFETY AND HEALTH PROTECTION:

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

More detailed information is provided on the label and in the safety data sheet, which is available upon request.



0.9l, 3.6l, 9l




8÷12 m²/l



1 h



water



The information in this document is given to the best of our knowledge, based on laboratory testing and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be used, therefore we cannot guarantee anything but the quality of the product itself in accord with applicable our quality control procedures. We reserve the right to change the given data without further notice. The new information and technical specifications you can find on www.rilak.lv Users should always consult RILAK for specific guidance on the general suitability of this product for their needs and specific application practices.