

SIA Rīgas laku un krāsu rūpnīca Product specification

# **MOVILAT 25**

## ACRYLIC WATER-BASED SEMI MATT PAINT FOR WALLS AND CEILINGS



- Designed for wall and ceiling finishing
- Suitable for residential, office, and public interiors
- Highly resistant to repeated washing
- Ideal for use in bathrooms and other humid areas

#### **DESCRIPTION:**

Fast-drying, waterborne acrylic paint for interior use, forming a durable semi-matt finish with a noticeable silky sheen. The product is easy to apply, highly resistant to moisture, and suitable for areas subject to frequent cleaning. The coating remains flexible, prevents cracking, and maintains an elegant appearance even after repeated washing.

#### FIELD OF APPLICATION:

Recommended for painting interior walls and ceilings in both dry and humid environments, including bathrooms, kitchens, hallways, living spaces, and offices. Suitable for use on concrete, plaster, brick, wood, gypsum board surfaces, as well as textured wallpapers designed for painting.

TECHNICAL PARAMETERS:	
<u>Colour:</u>	White (A base) which may be tinted in to light shades. C base may be tinted to dark shades using RILAKOLOR tinting system.
<u>Gloss:</u>	Semi-matt with a silky (satin) sheen
Drying time at 20ºC temperature and the relative air humidity 50 %:	1 hour
Solids contents, %	Base A: $60 \pm 4$ ; base C: $41 \pm 4$ .
Resistance to wet friction:	Class 1 (ISO 11998)
Consumption:	8÷12 m²/l
<u>Solvent:</u>	Water
Tools used for application:	Brush, roller, paint sprayer.
<u>Storage period</u> :	36 months in tightly closed manufacturer's container at the temperature exceeding +5°C.
Packaging:	0.9 l; 3.6 l; 9 l.



### APPLICATION: PREPARATION OF PAINT FOR USE:

Mix paint well before application. Dilute with water till required viscosity, if necessary.

#### **PREPARATION OF SURFACE:**

Clean off any dust, dirt, chalk, previously painted coat of glue paint or other type of old flaked paint. Treat the oil- or alkyd-painted surfaces with sandpaper until light-matte appearance is reached. If there is mold or another fungal infection, treat it with AKVASEPT solution.

#### **PRIMING OF SURFACE:**

Porous plaster and concrete surfaces should be primed using MOVILAT PRIMER, FORAKRIL BASE, AKROPRIM. MOVILAT 25 itself can also be used as a primer diluted by water up to 15% of the paint volume.

#### **APPLICATION:**

Apply 2 layers to surfaces to be painted. Application of 1 - 2 layers is recommended in case of repainting of the previously painted surfaces. Air and painted surface temperature may not be lower than +  $5^{\circ}$ C and higher than +  $30^{\circ}$ C.

#### SURFACE TREATMENT:

After 30 days, the painted surface is washable using soft cleaning agents. Clean with a soft cloth or sponge dampened with water or a mild alkaline detergent. After using cleaning agents, rinse the surface with clean water and dry with a cloth. A slight change in sheen may occur with repeated cleaning.

#### **TOOL CLEANING:**

Use water for cleaning of tools.

#### ENVIRONMENT AND OCCUPATIONAL SAFETY AND HEALTH PROTECTION:

Keep out of reach of children.Avoid breathing dust/fume/gas/mist/vapours/spray.IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, ifpresent and easy to do. Continue rinsing.

More detailed information is provided on the label and in the safety data sheet, which is available upon request.



The information in this document is given to the best of our knowledge, based on laboratory testing and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be used, therefore we cannot guarantee anything but the quality of the product itself in accord with applicable our quality control procedures. We reserve the right to change the given data without further notice. The new information and technical specifications you can find on www.rilak.lv Users should always consult RILAK for specific guidance on the general suitability of this product for their needs and specific application practices.

Rīgas laku un krāsu rūpnīca 63/65 Daugavgrivas Street, Riga, LV-1007, Tel.: (+371) 67459117, Fax: (+371) 67614542

#### www.rilak.lv