

MOVILAT 7

ACRYLIC WATER-BASED MATT PAINT FOR WALLS AND CEILINGS



- Matt paint with slight silk gloss
- Suitable for wet rooms
- Easy-to-wash
- Great spreading capacity
- Fast drying
- Non-dripping, easy-to-apply

DESCRIPTION:

Fast-drying easy-to-apply water-based paint. Paint forms silky matt film with high degree of washability therefore it is suitable for application in humid rooms like bathrooms etc. The paint is characterised by good spreading capacity and resistance to cleaning solutions. It may be tinted to many shades.

FIELD OF APPLICATION:

Paint is intended for painting of walls and ceilings in dry residential, office, public, etc. areas, as well as in rooms with increased humidity such as bathrooms, toilets, etc. May be used for painting of plaster, concrete, brick and gypsum board and embossed acrylic, vinyl and fibreglass wallpapers, as well as wood-fibre and wood particleboards. This paint may be also applied on primed metal and other surfaces previously painted with water-based paints.

TECHNICAL PARAMETERS:	
<u>Colour:</u>	White (A base) which may be tinted in to light shades. C base may be tinted to dark shades using RILAKOLOR tinting system.
<u>Gloss:</u>	Matt with slight silk gloss.
<u>Drying time at 20°C temperature and the relative air humidity 50 %:</u>	1 hour
<u>solids contents, %</u>	Base A: 52 ± 3; base C: 60 ± 3.
<u>Resistance to wet friction:</u>	Class 1 (ISO 11998)
<u>Consumption:</u>	8÷12 m ² /l
<u>Solvent:</u>	Water
<u>Tools used for application:</u>	Brush, roller, paint sprayer.
<u>Storage period:</u>	36 months in tightly closed manufacturer's container at the temperature exceeding +5°C.
<u>Packaging:</u>	0.9 l; 3.6 l; 9 l.

APPLICATION:

PREPARATION OF PAINT FOR USE:

Mix paint well before application. Dilute with water till required viscosity, if necessary.

PREPARATION OF SURFACE:

Clean off any dust, dirt, chalk, previously painted coat of glue paint or other type of old flaked paint. Treat the oil- or alkyd-painted surfaces with sandpaper until light-matte appearance is reached. If there is mold or another fungal infection, treat it with AKVASEPT solution.

PRIMING OF SURFACE:

Porous plaster and concrete surfaces should be primed using MOVILAT PRIMER, FORAKRIL BASE, AKROPRIM. MOVILAT 7 itself can also be used as a primer diluted by water up to 15% of the paint volume.

APPLICATION:

Apply 2 layers to surfaces to be painted. Application of 1 - 2 layers is recommended in case of repainting of the previously painted surfaces. Air and painted surface temperature may not be lower than + 5°C and higher than + 30°C.

SURFACE TREATMENT:

Cleaning of fresh painted surface is allowed not earlier than one week after painting. A cloth soft or sponge dampened with clean water or weak alkaline cleaning solution may be used for cleaning of the surface. Do not use abrasive cleaners to clean the painted surface.

TOOL CLEANING:

Use water for cleaning of tools.

ENVIRONMENT AND OCCUPATIONAL SAFETY AND HEALTH PROTECTION:

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



0.9l, 3.6, 9l




8÷12 m²/l



1 h



RILAKOLOR
(A, C base)



The information in this document is given to the best of our knowledge, based on laboratory testing and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be used, therefore we cannot guarantee anything but the quality of the product itself in accord with applicable our quality control procedures. We reserve the right to change the given data without further notice. The new information and technical specifications you can find on www.rilak.lv Users should always consult RILAK for specific guidance on the general suitability of this product for their needs and specific application practices.