



PENTAPRIM

UNIVERSAL ALKYD ENAMEL



- For wood and metal
- Easy application
- Has 23 standard colours

DESCRIPTION:

Easy-to-apply universal weather-resistant gloss enamel with excellent adhesion to various substrates, including new and previously painted metal and wooden surfaces for outdoors and indoors. Enamel is characterised by long lasting gloss, good mechanical resistance.

FIELD OF APPLICATION:

Paint is intended for painting of wooden, primed metal surfaces, wooden-fibre and particleboards both during interior and exterior works. May be used for painting of various wooden and metal objects and structures.

<u>TECHNICAL PARAMETERS:</u>	
<u>Colour:</u>	Prime Colors: white, red, orange, yellow, green, light-blue, blue, ivory, cream, salmon, beige, terracotta, yellow-brown, red-brown, brown, chery, saladgreen, light-green, khaki, light-grey, grey, antracit, black)
<u>Gloss:</u>	Gloss
<u>Drying time at 20°C temperature:</u>	Not more than 24 hours.
<u>Solids by weight, %</u>	42 ± 2 (for white color)
<u>Consumption:</u>	8÷12 m ² /l for one layer.
<u>Solvent:</u>	VAITSOL, white spirit
<u>Tools used for application:</u>	Brush, roller, paint sprayer.
<u>Storage period:</u>	36 months in tightly closed manufacturer's container at the temperature exceeding 0°C.
<u>Packaging:</u>	0.45 l; 0.9 l; 2.7 l; 10 l



APPLICATION:

PREPARATION OF PAINT FOR USE:

Mix paint well before application. If necessary, dilute with solvent till required viscosity using solvent up to 0-4% of the volume if applied by brush or roller.

PREPARATION OF SURFACE:

Remove dust, various dirt contaminants and flakes paint. Remove rust from the metal surfaces. Sand glossy surfaces with sandpaper until light-matte appearance is reached.

PRIMING OF SURFACE:

For priming of steel surfaces, we recommend to use the primers GF-021, NOVAKOR, NEOSPRINT PRIMER, RIATOP PRIMER. Treat aluminium and zinc-galvanized surfaces with primers VL-02 or NEOSPRINT PRIMER.

For new wooden surfaces intended to be used in open environment: Before painting, treat them with colour less TEKSTURDEKOR or WOOD PROTECT.

APPLICATION:

Apply enamel on to clean and dry surfaces in 1-2 layers with brush, roller, spray or airless spray (nozzle diameter 0,011" - 0,017"). Air temperature during painting and drying of paint may not be lower than + 5°C. Relative air humidity - not higher than 85%. Application of enamel by spraying is allowed only in painting departments of industrial productions and workshops.

TOOL CLEANING:

Use VAITSOL or white spirit solvent for cleaning of tools.

ENVIRONMENT AND OCCUPATIONAL SAFETY AND HEALTH PROTECTION:

Contains White Spirit. Flammable liquid and vapour. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Store in a well-ventilated place. Keep container tightly closed.



0.45l, 0.9l,
2.7l, 10l



8÷12 m²/l



24 h



VAITSOL,
white spirit



The information in this document is given to the best of our knowledge, based on laboratory testing and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be used, therefore we cannot guarantee anything but the quality of the product itself in accord with applicable our quality control procedures. We reserve the right to change the given data without further notice. The new information and technical specifications you can find on www.rilak.lv Users should always consult RILAK for specific guidance on the general suitability of this product for their needs and specific application practices.