



MOVILAT PRIMER

ACRYLIC WATER-BASED PRIMER-PAINT



- Universal primer for walls, ceilings, and metal
- Suitable for both dry and damp areas
- Can be used as a standalone coating
- Compatible with water-dispersible paints and enamels by RILAK
- Forms a moisture-resistant matte finish

DESCRIPTION:

Fast -drying, easy-to-apply water-based primer-paint based on a special acrylic dispersion. It is used as a traditional primer and also as a standalone coating for walls and ceilings. It forms a moisture-resistant, visually pleasing, deeply matte finish that is resistant to wet cleaning. Classified as Class 3 wet abrasion resistance according to ISO 11998.

FIELD OF APPLICATION:

Intended for priming plastered, concrete, wooden, brick, gypsum board walls and ceilings in all types of indoor environments (dry, damp, high-traffic, etc.), as well as ferrous and galvanized metal surfaces before applying water-dispersible paints and enamels such as MOVILAT AntiBacterial, Interior Professional 4, Interior Professional 7, MOVILAT 4, MOVILAT 7, MOVILAT 12, MOVILAT 25, and ENAMEL AQUA UNIVERSAL. It can also be used as a standalone coating when painting walls and ceilings in high-traffic areas such as residential premises, offices, etc. (without a top coat). Suitable for painting textured acrylic and fiberglass wallpapers.

<u>TECHNICAL PARAMETERS:</u>	
<u>Colour:</u>	Base A can be used as a white paint or tinted to light colors using the RILAKOLOR tinting system. When using MOVILAT PRIMER as a tinted primer, some color deviation from the topcoat shade may occur.
<u>Gloss:</u>	Matt
<u>Drying time at 20°C temperature and the relative air humidity 50 %:</u>	1 hour
<u>Solids contents, %</u>	58 ± 3
<u>Resistance to wet friction:</u>	Class 3 (ISO 11998)
<u>Consumption:</u>	8÷12 m ² /l
<u>Solvent:</u>	Water
<u>Tools used for application:</u>	Brush, roller, paint sprayer.
<u>Storage period:</u>	36 months in tightly closed manufacturer's container at the temperature exceeding +5°C.
<u>Packaging:</u>	0.9 l; 3.6 l; 9 l.

APPLICATION:

PREPARATION OF PAINT FOR USE:

Mix paint well before application. Dilute with water till required viscosity, if necessary.

PREPARATION OF SURFACE:

The surface to be painted must be dry, free of grease (oil stains), and clean. When painting aged wood, it is recommended to disinfect with AKVASEPT solution. Previously unpainted ferrous metal surfaces must be prepared to a minimum of St2 or Sa 2½ standard.

APPLICATION:

Apply with a brush, roller, spray gun, or airless spraying equipment in 1–2 coats at an air and surface temperature of at least +5°C. Drying time at +20°C is approximately 1 hour. Subsequent coats on mineral surfaces may be applied after 2 hours. Recoating primed ferrous or galvanized surfaces is permitted after 24 hours for ENAMEL AQUA UNIVERSAL enamels or after 48 hours for MOVILAT series paints.

TOOL CLEANING:

Use water for cleaning of tools.

ENVIRONMENT AND OCCUPATIONAL SAFETY AND HEALTH PROTECTION:

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



0.9l, 3.6, 9l




8÷12 m²/l



1 h



RILAKOLOR
(A base)



The information in this document is given to the best of our knowledge, based on laboratory testing and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be used, therefore we cannot guarantee anything but the quality of the product itself in accord with applicable our quality control procedures. We reserve the right to change the given data without further notice. The new information and technical specifications you can find on www.rilak.lv Users should always consult RILAK for specific guidance on the general suitability of this product for their needs and specific application practices.